



TECHNICAL DATA

TD-1356

PRODUCT NAME

PRODUCT NO.

INTERIOR ACRYLIC LATEX PAINT – EGGSHELL FINISH.

173-XXX

DESCRIPTION

Washable, non-yellowing low gloss paint with a rich silky sheen slightly higher than flat.
Perfect paint for walls and ceilings in living rooms, dining rooms, halls and bedrooms.

INTENDED USES

Interior.
New or maintenance work.
Primed materials: gypsum or fibre wallboards, wood, plaster, metal, concrete, concrete blocks, acoustical tiles, wallpaper.
Walls and ceilings.
Homes, institutions, hospitals, commercial or public buildings.

REMARK: For kitchens and bathrooms, a pearl, melamine or semi-gloss finish is preferable.

ADVANTAGES

Washable.
High viscosity and ultra hiding.
Ready for use and easy to apply.
Dries rapidly with a minimum of odour.
Non-spattering.
Soft, smooth finish with subdued gloss.
Complete range of colours.
Ecological product containing neither lead nor mercury and featuring the Canadian Environmental ECOLOGO as approved by the Canadian Standard Association (CSA).

SURFACE PREPARATION

PROPER SURFACE PREPARATION IS IMPORTANT PARTICULARLY IN KITCHENS AND BATHROOMS.

The surface must be dry, clean, free from dust, oil, grease, soap, wax, mildew, rust, loose paint, etc.
Wash the surface with a concentrated solution of trisodium phosphate (T.S.P.) POLYPREP 771-137.
Rinse well with clear water.

Mildew: Wash with bleach water. (1:3 bleach water: water)

Glossy surfaces: Sand lightly.

Loose paint: Scrape and sand. Prime bare spots with recommended primer. Repair cracks and loose joints.

Bare wood: Seal knots and sap streaks with transparent shellac POLYPREP 205-112 or white-pigmented POLYPREP 2 (145-022).

Rust: Remove with CORROSTOP ULTRA 635-104 metal conditioner and rust remover.

TD-1356

TECHNICAL GUIDE

VISCOSITY:	Ready for use.	COLOURS:	Titanium white 173-510, natural white 173-501, medium base 173-502, neutral base 173-503, yellow base 173-504 and red base 173-505.
FLASH POINT:	Non-flammable.	TINTING:	Can be tinted to Sico 4000 colour system.
GLOSS (60°):	5 to 12%	COMPOSITION:	Modified acrylic latex (binder), titanium dioxide and inert extenders (pigments), water (volatile matter), surfactants (agents) and others.
REFLECTS (85°):	25 to 35%	STORAGE:	Keep between 4°C (40°F) and 26°C (80°F) in a safe and well-ventilated place. Avoid freezing.
DRYING TIME:	1 to 2 hours.		
RECOATING:	4 to 6 hours. Vary according to temperature and relative humidity.		
SPREADING RATE:	10 to 12 square metres (110 to 130 sq. ft.) per litre depending on porosity and texture of the surface.	THINNER/ CLEANER:	Water
SIZES:	18.9 litres for 173-501. 3.78 litres and 946 ml for all products.	APPLICATION TOOLS:	Brush, roller or spray gun. Preferably a roller for large surfaces and a synthetic bristle (nylon/polyester) brush for cutting in and trim.
SPECIFICATIONS:	Meets Canadian Specification 1.209-93. Qualification number: 80235.		Wash tools in warm soapy water immediately after use.

RECOMMENDED PRIMER

Bare wood: Apply one coat of alkyd primer SICO CLASSIC 180-110 or latex 170-125.

Gypsum board, dry new plaster, concrete and concrete blocks: Apply one coat of latex primer SICO CLASSIC 170-125.

Old plaster: Apply one coat of alkyd primer SICO CLASSIC 180-110.

Ferrous metal: Apply one coat of CORROSTOP ULTRA anti-corrosion primer 635-260 or 635-785.

Painted surfaces and plaster repairs: Apply one coat of alkyd primer SICO CLASSIC 180-110 or latex 170-125.

APPLICATION

Ready for use. No thinning required. Stir thoroughly before using.

Apply generously in even coats. Provide adequate ventilation during application and drying.

Two finishing coats give a better durability and appearance.

Application temperature: Minimum 10°C (50°F), maximum 32°C (90°F).

Let dry thoroughly between coats.

Washing instructions: Allow to dry fourteen (14) days before washing. Soil and most household stains can be removed using a soft cloth or sponge and a concentrated solution of trisodium phosphate (T.S.P.) POLYPREP 771-137.

RESTRICTIONS

Do not use for exterior work.

Do not use on floors.

SAFETY PRECAUTIONS

Do not swallow. Do not get in eyes or on skin. Wear safety glasses.

FIRST AID TREATMENT: If swallowed, call a Poison Control Centre or doctor immediately. If in eyes or on skin, rinse well with water.

Keep out of reach of children.

Paint disposal: Contact your municipality about proper paint disposal procedure.