



## TECHNICAL DATA

TD-1367

### PRODUCT NAME

### PRODUCT NO.

INTERIOR ACRYLIC LATEX PAINT – PEARL FINISH – SUPER LATEX.

176-XXX

### DESCRIPTION

Interior latex finish suitable for walls, woodworks and doors of any room of the house.  
Subdued reflection when viewed straight on and semi-gloss when viewed at a grazing angle.

### INTENDED USES

Interior.  
New or maintenance work.  
Primed materials: gypsum or fibre wallboards, wood, plaster, metal, concrete, concrete blocks, acoustical tiles, wallpaper.  
Walls, woodworks, doors, cabinets.  
Any room in the house, institutions, schools, hospitals, commercial and public buildings.

### ADVANTAGES

Ultra washable and long-lasting.  
High viscosity and ultra hiding.  
Ready for use and easy to apply.  
Non-spattering.  
Dries rapidly with a minimum of odour.  
Excellent resistance to washing, scrubbing and yellowing.  
Complete range of colours.  
Soft, smooth, glare-free finish.  
Ecological product containing neither lead nor mercury and featuring the Canadian Environmental ECOLOGO as approved by the Canadian Standard Association (CSA).

### SURFACE PREPARATION

PROPER SURFACE PREPARATION IS IMPORTANT PARTICULARLY IN KITCHENS AND BATHROOMS.  
The surface must be dry, clean and free from dust, oil, grease, soap, wax, mildew, rust, loose paint, etc.  
Before painting, wash the surface well with a concentrated solution of trisodium phosphate (T.S.P.) POLYPREP 771-137. Rinse well with clear water.  
Mildew: Wash with bleach water. (1:3 bleach water: water)  
Glossy surfaces: Sand lightly.  
Bare wood: Seal knots and sap streaks with transparent shellac POLYPREP 205-112 or white-pigmented POLYPREP 2 (145-022).  
Loose paint: Scrape, then sand. Prime bare spots with recommended primer. Repair cracks and loose joints.  
Rust: Remove with CORROSTOP ULTRA 635-104 metal conditioner and rust remover.

TD-1367

## TECHNICAL GUIDE

<b>VISCOSITY:</b>	Ready for use.	<b>COLOURS:</b>	Titanium white 176-510, natural white 176-501, medium base 176-502, neutral base 176-503, yellow base 176-504 and red base 176-505.
<b>FLASH POINT:</b>	Non-flammable.	<b>TINTING:</b>	Can be tinted to Sico 4000 colour system.
<b>GLOSS (60°):</b>	22 to 30%	<b>COMPOSITION:</b>	Modified acrylic latex (binder), titanium dioxide and inert extenders (pigments), water (volatile matter), surfactants (agents) and others.
<b>REFLECTS (85°):</b>	60 to 70%	<b>STORAGE:</b>	Keep between 4°C (40°F) and 26°C (80°F) in a safe and well-ventilated place.
<b>DRYING TIME:</b>	2 to 4 hours.		
<b>RECOATING:</b>	4 to 6 hours. Vary according to temperature and relative humidity.		Avoid freezing.
<b>SPREADING RATE:</b>	11 to 13 square metres (120 to 140 sq. ft.) per litre depending on porosity and texture of the surface.	<b>THINNER/ CLEANER:</b>	Water.
<b>SIZES:</b>	18.9 litres for 176-501. 3.78 litres and 946 ml for all products.	<b>APPLICATION TOOLS:</b>	Brush, roller or spray gun. Preferably a roller for large surfaces and a synthetic bristle (nylon/polyester) brush for cutting in and trim.
<b>SPECIFICATIONS:</b>	None.		Wash tools in warm soapy water immediately after use.

## RECOMMENDED PRIMER

Bare wood: Apply one coat of alkyd primer SICO CLASSIC 180-110 or latex 170-125.

Gypsum board, dry new plaster, concrete and concrete blocks: Apply one coat of latex primer CLASSIC 170-125.

Previously painted surfaces and plaster repairs: Apply one coat of alkyd primer CLASSIC 180-110 or latex 170-125.

Old plaster: Apply one coat of alkyd primer SICO CLASSIC 180-110.

Ferrous metal: Apply one coat of CORROSTOP ULTRA anti-corrosion primer 635-260 or 635-785.

## APPLICATION

Ready for use. No thinning required.

Stir thoroughly before using. Apply generously and evenly.

Provide adequate ventilation during application and drying.

Allow to dry completely before recoating.

Two finishing coats give a better durability and appearance.

Application temperature: Minimum 10°C (50°F), maximum 32°C (90°F).

Washing instructions: Allow to dry fourteen (14) days before washing. Soil and most household stains can be removed using a soft cloth or sponge and a concentrated solution of trisodium phosphate (T.S.P.) POLYPREP 771-137.

## RESTRICTIONS

Do not use for exterior work.

Do not use on floors.

## SAFETY PRECAUTIONS

Do not swallow. Do not get in eyes or on skin. Wear safety glasses.

**FIRST AID TREATMENT:** If swallowed, call a Poison Control Centre or doctor immediately. If in eyes or on skin, rinse well with water.

Keep out of reach of children.

Paint disposal: Contact your municipality about proper paint disposal procedure.