



TECHNICAL DATA

TD-1865

PRODUCT NAME

PRODUCT NO.

INTERIOR ACRYLIC LATEX PAINT – FLAT FINISH – SUPER LATEX.

711-50X

DESCRIPTION

A flat latex finish for walls and ceilings of bedrooms, family rooms, living room.
Flat appearance when viewed straight on and satin reflection when viewed at a grazing angle.

INTENDED USES

Interior.
New work or maintenance.
Primed materials: gypsum or fiber wallboards, wood, plaster, metal, concrete, concrete blocks, acoustical tiles, wallpaper.
Walls and ceilings.
Homes, institutions, hospitals, commercial or public buildings.

REMARK: For surfaces requiring frequent cleanings, platinum finish 714-, pearl finish 716-, semi-gloss 717- or melamine 166- series is recommended.

ADVANTAGES

Washable.
High viscosity and ultra hiding.
Ready for use and easy to apply.
Dries rapidly with a minimum of odor.
Non-spattering.
Complete range of colors.
Ecological product containing no lead no mercury and featuring the Canadian Environmental ECOLOGO as approved by the Canadian Standard Association (CSA).

SURFACE PREPARATION

PROPER SURFACE PREPARATION IS IMPORTANT PARTICULARLY IN THE KITCHENS AND THE BATHROOMS.
The surface must be dry, clean and free from dust, oil, grease, soap, wax, mildew, rust, loose paint, etc.
Seals imperfections with spackling compound.
Wash the surface well before painting with a concentrated solution of trisodium phosphate (T.S.P.) POLYPREP 771-137.
Rinse well with clear water.
Mildew: wash with a household bleach solution. (1:3 household bleach: water)
Glossy surfaces: sand lightly.
Bare wood: seal knots and sap streaks with transparent shellac POLYPREP 205-112 or white pigmented POLYPREP 2 (145-022).
Loose paint: scrape, then sand. Prime bare spots with recommended primer. Repair cracks and loose joints.
Rust: remove with CORROSTOP ULTRA 635-104 metal conditioner and rust remover.

TECHNICAL GUIDE

VISCOSITY:	Ready for use.	COLORS:	Super white 711-110, natural white 711-501, intermediate base 711-502, neutral 711-503, yellow 711-504 and red 711-505.
FLASH POINT:	Non-flammable.	TINTING:	Can be tinted to Sico 4000 colors system.
GLOSS (60°):	0 to 5%	COMPOSITION:	Modified acrylic latex (binder), titanium dioxide and inert extenders (pigments), water (volatile matter), surfactant (agents) and others.
REFLECTS (85°):	about 10%	STORAGE:	Keep between 4°C (40°F) and 26°C (80°F) in a safe and well ventilated place.
DRYING TIME:	20 to 30 minutes (to touch) 30 to 60 minutes (tack free) 4 hours (recoat) Varies according to temperature and relative humidity.		Avoid freezing.
SPREADING RATE:	11 to 13 m ² (120 to 140 sq. ft.) per litre depending on porosity and texture of the surface.	THINNER:	Water
SIZES:	3.78 litres and 946 ml	APPLICATION TOOLS:	Brush, roller or spray gun. Preferable a roller for large surfaces and a synthetic bristle (nylon/polyester) brush for trim.
SPECIFICATIONS:	Type CAN/CGSB – 1.100-M89.		Wash tools in warm soapy water immediately after use.

RECOMMENDED PRIMER

Bare wood: Apply one coat of alkyd primer SICO SUPREME 720-110 or latex 710-120.

Dry new plaster, gypsum board, concrete and concrete blocks: Apply one coat of latex primer SICO SUPREME 710-120.

Previously painted surfaces, plaster repairs: Apply one coat of alkyd primer SICO SUPREME 720-110 or latex 710-120.

Old plaster: Apply one coat of alkyd primer SICO SUPREME 720-110.

Ferrous metal: Apply one coat of CORROSTOP ULTRA anti-corrosion primer 635-260 or 635-785.

APPLICATION

Ready for use. No thinning required.

Stir thoroughly before using. Apply generously and evenly.

Application temperature: 10°C (50°F) minimum, 32°C (90°F) maximum.

LET DRY THOROUGHLY BETWEEN COATS.

WASHING INSTRUCTIONS: to assure maximum washability and durability, wait at least two weeks (14 days) before washing the dry paint film. When removing stains, dirt and marks, use a soft cloth or sponge with water or a general purpose household cleaner (trisodium phosphate) POLYPREP 771-137. Rinse with wet rag and dry with dry rag. Do not use abrasive, corrosive cleaner or scrub brush to remove stains.

RESTRICTIONS

Do not use for exterior work.

Do not use on floors.

SAFETY PRECAUTIONS

Keep out of reach of children.

Provide adequate ventilation during application and drying.

Keep containers closed when not in use.

Paint disposal: contact your municipality about proper paint disposal procedure.