



TECHNICAL DATA

TD-1856

PRODUCT NAME

PRODUCT NO.

INTERIOR ACRYLIC LATEX PAINT – EGGSHELL FINISH.

713-XXX

DESCRIPTION

Washable, non-yellowing low gloss paint with a rich silky sheen slightly higher than flat.
Perfect paint for walls and woodwork in living rooms, dining rooms, halls and bedrooms.

INTENDED USES

Interior.
New or maintenance work.
Primed materials: gypsum or fibre wallboards, wood, plaster, metal, concrete, concrete blocks, acoustical tiles, wallpaper.
Walls, ceilings and woodwork.
Homes, hospitals, commercial or public buildings.

REMARK: For kitchens and bathrooms, a pearl, platinum, melamine or semi-gloss finish is preferable.

ADVANTAGES

Washable.
High viscosity and ultra hiding.
Ready for use and easy to apply.
Dries rapidly with a minimum of odor.
Non-spattering.
Soft, smooth finish with subdued gloss.
Complete range of colors.
Ecological product containing neither lead nor mercury and featuring the Canadian Environmental ECOLOGO as approved by the Canadian Standard Association (CSA).

SURFACE PREPARATION

PROPER SURFACE PREPARATION IS IMPORTANT PARTICULARLY IN KITCHENS AND BATHROOMS.

The surface must be dry, clean, free from dust, oil, grease, soap, wax, mildew, rust, loose paint, etc.
Wash the surface with a concentrated solution of trisodium phosphate (T.S.P.) POLYPREP 771-137.

Rinse well with clear water.

Mildew: Wash with a household bleach solution. (1:3 household bleach: water)

Glossy surfaces: Sand lightly.

Loose paint: Scrape and sand. Prime bare spots with recommended primer. Repair cracks and loose joints.

Bare wood: Seal knots and sap streaks with transparent shellac POLYPREP 205-112 or white-pigmented POLYPREP 2 (145-022).

Rust: Remove with CORROSTOP ULTRA 635-104 metal conditioner and rust remover.

TD-1856

TECHNICAL GUIDE

VISCOSITY:	Ready for use.	COLORS:	Super white 713-110, natural white 713-501 and intermediate base 713-502, neutral 713-503, yellow 713-504 and red 713-505.
FLASH POINT:	Non-flammable.	TINTING:	Can be tinted to Sico 4000 color system.
GLOSS (60°):	5 to 12%	COMPOSITION:	Modified acrylic latex (binder), titanium dioxide and inert extenders (pigments), water (volatile matter), surfactants (agents) and others.
REFLECTS (85°):	20 to 30%	STORAGE:	Keep between 4°C (40°F) and 26°C (80°F) in a safe and well-ventilated place. Avoid freezing.
DRYING TIME:	20 to 30 minutes (to touch) 30 to 60 minutes (tack free) 4 hours (recoat) Varies according to temperature and relative humidity.	THINNER:	Water.
SPREADING RATE:	11 to 13 m ² (120 to 140 sq. ft.) per litre depending on porosity and texture of the surface.	APPLICATION TOOLS:	Brush, roller or spray gun. Preferably a roller for large surfaces and a synthetic bristle (nylon/polyester) brush for trim.
SIZES:	3.78 litres and 946 ml		Wash tools in warm soapy water immediately after use.
SPECIFICATIONS:	Meets Canadian Specification 1.209-93. Qualification number: 80235.		

RECOMMENDED PRIMER

Bare wood: Apply one coat of alkyd primer SICO SUPREME 720-110 or latex 710-120.

Gypsum board, dry new plaster, concrete and concrete blocks: Apply one coat of latex primer SICO SUPREME 710-120.

Old plaster: Apply one coat of alkyd primer SICO SUPREME 720-110.

Ferrous metal: Apply one coat of CORROSTOP ULTRA anti-corrosion primer 635-260 or 635-785.

Painted surfaces and plaster repairs: Apply one coat of alkyd primer SICO SUPREME 720-110 or latex 710-120.

APPLICATION

Ready for use. No thinning required.

Stir thoroughly before using. Apply generously and evenly.

Application temperature: minimum 10°C (50°F), maximum 32°C (90°F).

LET DRY THOROUGHLY BEFORE BETWEEN COATS.

RESTRICTIONS

Do not use for exterior work.

Do not use on floors.

SAFETY PRECAUTIONS

Keep out of reach of children.

Provide adequate ventilation during application and drying.

Keep containers closed when not in use.

Paint disposal: contact your municipality about proper paint disposal procedure.