



## TECHNICAL DATA

TD-1854

### PRODUCT NAME

### PRODUCT NO.

INTERIOR ACRYLIC LATEX PAINT – PEARL FINISH – SUPER LATEX.

716-XXX

### DESCRIPTION

Interior latex finish suitable for walls and ceilings of any room of the house.  
Subdued reflection when viewed straight on and semi-gloss when viewed at a grazing angle.

### INTENDED USES

Interior.  
New work or maintenance.  
Primed materials: gypsum or fibre wallboards, wood, plaster, metal, concrete, concrete blocks, acoustical tiles, wallpaper.  
Walls, ceilings, woodworks, doors, cabinets.  
Any room in the house, institutions, schools, hospitals, commercial and public buildings.

### ADVANTAGES

Ultra washable.  
High viscosity and ultra hiding.  
Ready for use and easy to apply.  
Dries rapidly with a minimum of odor.  
Excellent resistance to washing, scrubbing and yellowing.  
Complete range of colors.  
Soft, smooth, glare-free finish.  
Ecological product containing no lead no mercury and featuring the Canadian Environmental ECOLOGO as approved by the Canadian Standard Association (CSA).

### SURFACE PREPARATION

PROPER SURFACE PREPARATION IS IMPORTANT PARTICULARLY IN THE KITCHENS AND THE BATHROOMS.  
The surface must be dry, clean and free from dust, oil, grease, soap, wax, mildew, rust, loose paint, etc.  
Wash the surface well before painting with a concentrated solution of trisodium phosphate (T.S.P.) POLYPREP 771-137.  
Rinse well with clear water.  
Mildew: wash with a household bleach solution. (1:3 household bleach: water)  
Glossy surfaces: sand lightly.  
Bare wood: seal knots and sap streaks with transparent shellac POLYPREP 205-112 or white pigmented POLYPREP 2 (145-022).  
Loose paint: scrape, then sand. Prime bare spots with recommended primer. Repair cracks and loose joints.  
Rust: remove with CORROSTOP ULTRA 635-104 metal conditioner and rust remover.

TD-1854

## TECHNICAL GUIDE

<b>VISCOSITY:</b>	Ready for use.	<b>COLORS:</b>	Super white 716-110, natural white 716-501 and the intermediate base 716-502, neutral 716-503, yellow 716-504 and red 716-505.
<b>FLASH POINT:</b>	Non-flammable.	<b>TINTING:</b>	Can be tinted to Sico 4000 colors system.
<b>GLOSS (60°):</b>	22 to 30%	<b>COMPOSITION:</b>	Modified acrylic latex (binder), titanium dioxide and inert extenders (pigments), water (volatile matter), surfactant (agents) and others.
<b>REFLECTS (85°):</b>	60 to 70%	<b>STORAGE:</b>	Keep between 4°C (40°F) and 26°C (80°F) in a safe and well ventilated place.  Avoid freezing.
<b>DRYING TIME:</b>	20 to 30 minutes (to touch) 2 to 4 hours (tack free) 4 to 6 hours (recoat) Varies according to temperature and relative humidity.	<b>THINNER:</b>	Water.
<b>SPREADING RATE:</b>	11 to 13 m <sup>2</sup> (120 to 140 sq. ft) by litre depending on porosity and texture of the surface.	<b>APPLICATION TOOLS:</b>	Brush, roller or spray gun. Preferable a roller for large surfaces and a synthetic bristle (nylon/polyester) brush for trim.
<b>SIZES:</b>	3.78 litres and 946 mL		Wash tools in warm soapy water immediately after use.
<b>SPECIFICATIONS:</b>	None.		

## RECOMMENDED PRIMER

Bare wood: Apply one coat of alkyd primer SICO SUPREME 720-110 or latex 710-120.

Gypsum boards, dry new plaster, concrete and concrete blocks: Apply one coat of latex primer SUPREME 710-120.

Previously painted surfaces and plaster repairs: Apply one coat of alkyd primer SUPREME 720-110 or latex 710-120.

Old plaster: Apply one coat of alkyd primer SICO SUPREME 720-110.

Ferrous metal: Apply one coat of CORROSTOP ULTRA anti-corrosion primer 635-260 or 635-785.

## APPLICATION

Ready for use. No thinning required.

Stir thoroughly before using. Apply generously and evenly.

Allow to dry completely before recoating.

A second finishing coat application insures a better durability and appearance.

Application temperature: minimum 10°C (50°F), maximum 32°C (90°F).

Washing instructions: allow to dry for seven (7) days before washing. Soil and most household stains can be removed using a soft cloth or sponge and a concentrated solution of trisodium phosphate (T.S.P.) POLYPREP 771-137.

## RESTRICTIONS

Do not use for exterior work.

Do not use on floors.

## SAFETY PRECAUTIONS

Keep out of reach of children.

Provide adequate ventilation during application and drying.

Keep containers closed when not in use.

Paint disposal: contact your municipality about proper paint disposal procedure.